RECEIVED CENTRAL FAX CENTER

JAN 2 2 2010

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application. Listing of Claims:

- 1. (Currently Amended) A composition consisting essentially of comprising
- (A) 100 parts by weight of at least one organosiloxane copolymer having a general formula (I) R¹_nSiO_{(4-n)/2}, where each R¹ is independently chosen from a hydrogen atom or a monovalent hydrocarbon group comprising 1 to 10 carbon atoms, provided greater than 80 mole percent of R¹ are methyl groups, n is a value from 0.8 to 1.5, greater than 50 mole percent of the copolymer comprises R¹SiO_{3/2} units, and having a hydroxyl content from 0.2 to 5 weight percent;
- (B) 10 to 120 parts by weight of at least one polyorganosiloxane having a general formula (II) R²R³₂SiO(R³₂SiO_{2/2})_a(R³SiO_{3/2})_bSiR³₂R² where each R² is an independently chosen hydrogen atom, monovalent hydrocarbon group comprising 1 to 10 carbon atoms, hydroxy group, or alkoxy group, each R³ is independently chosen from a hydrogen atom or a monovalent hydrocarbon group comprising 1 to 10 carbon atoms, a is an integer from 2 to 2000, and b is chosen such that b/(a+b) is from 0 to 0.05; and
- (C) 10 to 150 parts by weight of at least one metal alkoxide, where the amount of Component C in the composition is equal to or greater than the amount of Component B.
- 2. (Original) The composition of claim 1 where each R¹ is independently chosen from alkyl groups comprising 1 to about 8 carbon atoms and n is a value from 1 to 1.5.

- 3. (Original) The composition of claim 1 where each R¹ is methyl, n is a value from 1 to 1.3, greater than 70 mole percent of the organosiloxane copolymer comprises R¹SiO_{3/2} units, and the organosiloxane copolymer comprises essentially no SiO_{4/2} units.
- 4. (Previously presented) The composition of claim 1 where each R² of component (B) is an independently chosen alkyl group comprising 1 to 8 carbon atoms.
- 5. (Previously presented) The composition of claim 1 where each R² is methyl.
- 6. (Previously presented) The composition of claim 1 where the metal alkoxide has the formula $M(OR^4)_4$, where M is titanium or zirconium and each R^4 is independently chosen from alkyl groups comprising 1 to 12 carbon atoms or hydroxylated alkyl groups comprising 1 to 12 carbon atoms and containing less than 4 hydroxyl groups.
- 7. (Previously presented) The composition of claim 1 where the metal alkoxide has the formula $M(OR^4)_4$, where M is titanium and each R^4 is an alkyl group comprising 6 to 12 carbon atoms.
- 8. (Currently amended) The composition of claim 1 further consisting essentially of comprising 50 to 140 parts by weight of component (C) per 100 parts by weight of component (A).
- 9. Cancelled
- 10. (Currently amended) The composition of claim 1 further comprising consisting essentially of(D) at least one carrier chosen from water, organic solvents, and silicone compounds.

Page 3 of 8

- 11. (Currently amended) The composition of claim 1 further consisting essentially of comprising (D) 10 to 400 parts by weight per 100 parts by weight of component (A) of at least one carrier chosen from water, organic solvents, and silicone compounds
- 12. (Currently Amended) The composition of claim 1 further comprising consisting essentially of (D) 40 to 200 parts by weight per 100 parts by weight of component (A) of at least one carrier chosen from water, organic solvents, and silicone compounds.
- 13. (Currently amended) A method of preparing a composition comprising consisting essentially of mixing
- (A) 100 parts by weight of at least one organosiloxane copolymer having a general formula (I) R¹_nSiO_{(4-n)/2}, where each R¹ is independently chosen from a hydrogen atom or a monovalent hydrocarbon group comprising 1 to 10 carbon atoms, provided greater than 80 mole percent of R¹ are methyl groups, n is a value from 0.8 to 1.5, greater than 50 mole percent of the copolymer comprises R¹SiO_{3/2} units, and having a hydroxyl content from 0.2 to 5 weight percent;
- (B) 10 to 120 parts by weight of at least one polyorganosiloxane having a general formula (II) R²R³₂SiO(R³₂SiO_{2/2})_a(R³SiO_{3/2})_bSiR³₂R² where each R² is an independently chosen hydrogen atom, monovalent hydrocarbon group comprising 1 to 10 carbon atoms, hydroxy group, or alkoxy group, each R³ is independently chosen from a hydrogen atom or a monovalent hydrocarbon group comprising 1 to 10 carbon atoms, a is an integer from 2 to 2000, and b is chosen such that b/(a+b) is from 0 to 0.05; and
- (C) 10 to 150 parts by weight of at least one metal alkoxide, where the amount of Component C in the composition is equal to or greater than the amount of Component B.

Page 4 of 8

- 14. (Currently amended) A method for treating substrates comprising applying the composition of claim 1-a composition comprising (A) 100 parts by weight of at least one organosiloxane copolymer having a general formula (I) R¹_nSiO_{(4-n)/2}, where each R¹ is independently chosen from a hydrogen atom or a monovalent hydrocarbon group comprising 1 to 10 carbon atoms, provided greater than 80 mole percent of R¹ are methyl groups, n is a value from 0.8 to 1.5, greater than 50 mole percent of the copolymer comprises R¹SiO_{3/2} units, and having a hydroxyl content from 0.2 to 5 weight percent;
- (B) 10 to 120 parts by weight of at least one polyorganosiloxane having a general formula (II) R²R³2SiO(R³2SiO_{2/2})_a(R³SiO_{3/2})_bSiR³2R² where each R² is an independently chosen hydrogen atom, monovalent hydrocarbon group comprising 1 to 10 carbon atoms, hydroxy group, or alkoxy group, each R³ is independently chosen from a hydrogen atom or a monovalent hydrocarbon group comprising 1 to 10 carbon atoms, a is an integer from 2 to 2000, and b is chosen such that b/(a+b) is from 0 to 0.05; and
- (C) 10 to 150 parts by weight of at least one metal alkoxide.

 where the amount of Component C in the composition is equal to or greater than the amount of

 Component B to a substrate chosen from leather, textile fabrics, fibers, and masonry.
- 15. (Currently amended) The method for treating substrates of claim 14 where the substrate is chosen from leather, wood, textile fabrics, and fibers, and masonry.
- 16. (Currently amended) The composition of claim 7 further consisting essentially of comprising (D) at least one carrier chosen from water, organic solvents, and silicone compounds.
- 17. (Currently amended) The method of claim 13 further consisting essentially of comprising (D) at least one carrier chosen from water, organic solvents, and silicone compounds.

Page 5 of 8

18. Cancelled

Page 6 of 8